



Specifications Ledvance LED  
Downlight Slim Round DN105 6W  
430lm 120D - 865 Daylight | 118mm

[View Product](#)

General Information

|                          |                                     |
|--------------------------|-------------------------------------|
| SKU                      | 233362                              |
| EAN                      | 4058075079014                       |
| Manufacturer Code        | 4058075079014                       |
| Brand                    | Ledvance                            |
| Manufacturer Name        | DL SLIM DN105 6W/6500K WT IP20 LEDV |
| Any Lamp all-in warranty | 3 Years                             |
| Average Lifetime (h)     | 30000                               |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x18              |
| Wattage                     | 6W                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 865 Daylight      |
| Colour temperature (Kelvin) | 6500 Daylight     |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                          |                                       |
|--------------------------|---------------------------------------|
| Light colour options     | Single Color                          |
| Driver Included          | Yes                                   |
| Beam Angle (degree)      | 120                                   |
| Luminous Flux (Lumen)    | 430lm                                 |
| Luminous Efficacy (lm/W) | 70                                    |
| Power factor             | >0.50                                 |
| Installation Depth (mm)  | 50                                    |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PC (Polycarbonate)                    |
| Suitable for Outdoor     | No                                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 105                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Operating Temperature  | -20 to +50                    |
| Housing                | PC (Polycarbonate)            |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | DOWNLIGHT SLIM                |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 30  |
| Diameter (mm) | 118 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process



Trustpilot

